

VILNIAUS AERODROMO NAUDOJIMO MINIMUMAI

OPERATING MINIMA FOR VILNIUS AERODROME

Artėjimo tūpti procedūra Approach procedure		Orlaivio greičio kategorija/Aircraft speed category			
		A	B	C	D
		DA(H), MDA(H) / RVR (FALS ¹ ir/and NALS ²)			
RWY 01	ILS CAT II	728' (133') R400	745' (150') R450	757' (162') R450	771' (176') R450
	ILS CAT I	819' (224') R550 R1200	831' (236') R550 R1200	863' (268') R600 R1300	873' (278') R600 R1300
	LPV	896' (301') R700 R1400	909' (314') R700 R1400	917' (322') R800 R1500	927' (332') R800 R1500
	LNAV/VNAV	930' (330') R800 R1500	940' (350') R900 R1500	950' (350') R900 R1600	960' (360') R900 R1600
	LOC	980' (380') R1000 R1500	980' (380') R1000 R1500	980' (380') R1000 R1700	980' (380') R1000 R1700
	LNAV	1050' (450') R1400 R1500	1050' (450') R1400 R1500	1050' (450') R1400 R2100	1050' (450') R1400 R2100
	VOR	1060' (470') R1500 R2100	1060' (470') R1500 R2100	1060' (470') R1900 R2600	1060' (470') R1900 R2600
RWY 19	ILS CAT I	917' (268') R600 R1300	930' (281') R650 R1400	938' (289') R650 R1400	948' (299') R650 R1400
	LPV	933' (284') R650 R1400	945' (296') R650 R1400	953' (304') R700 R1400	964' (315') R700 R1400
	LNAV/VNAV	940' (290') R650 R1400	950' (300') R650 R1400	960' (310') R700 R1400	970' (320') R700 R1400
	LOC	1050' (400') R1000 R1500	1050' (400') R1000 R1500	1050' (400') R1000 R1800	1050' (400') R1000 R1800
	LNAV	1070' (420') R1200 R1500	1070' (420') R1200 R1500	1070' (420') R1200 R1900	1070' (420') R1200 R1900
	VOR	1190' (540') R1500 R2100	1190' (540') R1500 R2100	1190' (540') R2100 R2800	1190' (540') R2100 R2800

¹FALS – visa artėjimo tūpti apšvietimo sistema/full approach lighting system²NALS – artėjimo tūpti apšvietimo sistemos nebuvimas/no approach lighting system