

PALANGOS AERODROMO NAUDOJIMO MINIMUMAI

OPERATING MINIMA FOR PALANGA AERODROME

Artėjimo tūpti procedūra <i>Approach procedure</i>		Orlaivio greičio kategorija/ <i>Aircraft speed category</i>			
		A	B	C	D
		DA(H), MDA(H) / RVR (FALS ¹ ir/and NALS ²)			
RWY 01	LPV	287' (254') R600 R1300	299' (266') R600 R1300	308' (275') R600 R1300	318' (285') R650 R1400
	LNAV/VNAV	300' (270') R600 R1300	320' (280') R600 R1300	320' (290') R650 R1400	340' (300') R650 R1400
	LNAV	430' (400') R1100 R1500	430' (400') R1100 R1500	430' (400') R1100 R1800	430' (400') R1100 R1800
	NDB	420' (390') R1100 R1500	420' (390') R1100 R1500	420' (390') R1100 R1800	420' (390') R1100 R1800
	NDB (kai negautas SDF/when SDF not received)	430' (400') R1300 R2000	430' (400') R1300 R2000	430' (400') R1500 R2200	430' (400') R1500 R2200
RWY 19	ILS CAT I	287' (255') R600 R1300	299' (267') R600 R1300	307' (275') R600 R1300	317' (285') R650 R1400
	LOC	410' (380') R1000 R1500	410' (380') R1000 R1500	410' (380') R1000 R1700	410' (380') R1000 R1700
	LNAV	420' (390') R1100 R1500	420' (390') R1100 R1500	420' (390') R1100 R1800	420' (390') R1100 R1800
	NDB	420' (390') R1100 R1500	420' (390') R1100 R1500	420' (390') R1100 R1800	420' (390') R1100 R1800
Artėjimas tūpti ratu <i>Circling Approach</i> matomumas, m/visibility, m		490' (450') 1500	740' (710') 3600	870' (840') 3600	Netaikoma <i>Not applicable</i>

¹FALS – visa artėjimo tūpti apšvietimo sistema/full approach lighting system²NALS – artėjimo tūpti apšvietimo sistemos nebuvimas/no approach lighting system