

ŠIAULIAI (EYSA)
TACAN
RWY 32R (MIL)

GS		Kts	80	100	120	140	160	180	DIST SQQ	5	4	3	2	1
FAF - MAPt 5.4 NM		min:sec	4:03	3:14	2:42	2:19	2:02	1:48	Altitude	2170	1850	1540	1220	910
Rate of descent (5.2%)		ft/min	415	520	625	730	835	940	Height	(1723)	(1403)	(1093)	(773)	(463)
	STRAIGHT-IN APPROACH			CIRCLING APPROACH										
	TACAN													
	MDA(H)	Full	ALS out	MDA(H)	Visibility									
A	800 (350)	RVR 1500m	RVR 2400m	880 (440)	1500m	A								
B				1160 (710)	2400m	B								
C		RVR 1700m	RVR 2600m	1260 (810)	3600m	C								
D				1350 (910)	4300m	E								
E														

TABULAR DESCRIPTION

TACAN INSTRUMENT APPROACH for MILITARY ACFT from IAFs (SQQ, ODASA)		
FIX/POINTS	COORDINATES	FIX FORMATION
EVEGA (HLDG)	55 52.87N 023 05.45E	BRG 082.01° / 10.91 NM SQQ
ODASA (IAF)	55 39.77N 023 24.17E	BRG 351.79° / 12.80 NM SQQ
SQQ TACAN (IAF)	55 52.54N 023 24.81E	
IF	55 44.36N 023 36.45E	BRG 311.37° / 10.50 NM SQQ
FAF	55 48.32N 023 30.83E	BRG 311.37° / 5.43 NM SQQ
MAPt	55 52.54N 023 24.81E	
THR RWY 32R	55 52.85N 023 24.64E	
Final approach descent angle: 3.00°		