
STANDARD DEPARTURE CHART INSTRUMENT (SID) - ICAO

TRANSITION ALT 5000

TWR 124.205
118.505
ATIS 129.055

KAUNAS (EYKA) RNAV RWY 26

GOJOM 1B, KAZLA 1B, OTNAV 1B, UGNIS 1B



Changes: EYTSA15 added.

©2019 ORO NAVIGACIJA

STANDARD DEPARTURE CHART INSTRUMENT (SID) - ICAO

TRANSITION ALT 5000

KAUNAS (EYKA) RNAV RWY 26

GOJOM 1B, KAZLA 1B, OTNAV 1B, UGNIS 1B

TABULAR DESCRIPTION

GOJOM 1B PDG 7.0% REQUIRED DUE TO OPERATIONAL REASONS UNTIL KA201

Serial Number	*Path Descriptor*	*Waypoint Identifier*	*Fly-over*	*Course/Track °M(°T)*	*Magnetic Variation*	*Distance (NM)*	*Turn Direction*	*Altitude (FT)/ Flight level*	*Speed (KT)*	*Navigation Specification*
001	CF	KA201	—	257(265.1)	8.2	5.7	—	+2500	-230	RNAV1
002	TF	GOJOM	—	279(287.2)	8.2	32.9	—	—	—	RNAV1

KAZLA 1B PDG 7.0% REQUIRED DUE TO OPERATIONAL REASONS UNTIL KA204

Serial Number	*Path Descriptor*	*Waypoint Identifier*	*Fly-over*	*Course/Track °M(°T)*	*Magnetic Variation*	*Distance (NM)*	*Turn Direction*	*Altitude (FT)/ Flight level*	*Speed (KT)*	*Navigation Specification*
001	CF	KA204	—	257(265.1)	8.2	11.3	—	+5000	-230	RNAV1
002	TF	KA205	—	171(179.7)	8.2	10.6	—	—	—	RNAV1
003	TF	KAZLA	—	214(222.5)	8.1	21.9	—	—	—	RNAV1

OTNAV 1B PDG 7.0% REQUIRED DUE TO OPERATIONAL REASONS UNTIL KA201

Serial Number	*Path Descriptor*	*Waypoint Identifier*	*Fly-over*	*Course/Track °M(°T)*	*Magnetic Variation*	*Distance (NM)*	*Turn Direction*	*Altitude (FT)/ Flight level*	*Speed (KT)*	*Navigation Specification*
001	CF	KA201	—	257(265.1)	8.2	5.7	—	+2500	-230	RNAV1
002	TF	KA202	—	347(354.9)	8.2	12.0	—	—	—	RNAV1
003	TF	KA203	—	077(084.8)	8.2	11.7	—	+FL120	—	RNAV1
004	TF	OTNAV	—	123(131.6)	8.6	22.1	—	—	—	RNAV1

UGNIS 1B PDG 7.0% REQUIRED DUE TO OPERATIONAL REASONS UNTIL KA201

Serial Number	*Path Descriptor*	*Waypoint Identifier*	*Fly-over*	*Course/Track °M(°T)*	*Magnetic Variation*	*Distance (NM)*	*Turn Direction*	*Altitude (FT)/ Flight level*	*Speed (KT)*	*Navigation Specification*
001	CF	KA201	—	257(265.1)	8.2	5.7	—	+2500	-230	RNAV1
002	TF	KA202	—	347(354.9)	8.2	12.0	—	—	—	RNAV1
003	TF	UGNIS	—	347(354.9)	8.5	18.8	—	—	—	RNAV1

WAYPOINT COORDINATES			
FIX/POINTS	**COORDINATES**	**FIX/POINTS**	**COORDINATES**
KA201	54 57 15.5N 023 53 31.8E	**GOJOM**	55 06 43.5N 022 58 51.0E
KA202	55 09 11.6N 023 51 40.0E	**KAZLA**	54 29 59.3N 023 18 33.8E
KA203	55 10 13.4N 024 11 59.6E	**OTNAV**	54 55 33.0N 024 40 36.0E
KA204	54 56 45.6N 023 43 51.2E	**UGNIS**	55 27 50.9N 023 48 44.5E
KA205	54 46 10.5N 023 43 56.9E	**KNA**	54 57 37.4N 024 03 59.1E

FOR DETAILED FLIGHT PROCEDURES REFER TO AIP EYKA AD 2.22

Changes: VAR; Procedures courses.

©2019 ORO NAVIGACIJA