Changes: COM FAILURE; VAR and date of VAR; Procedures courses; note.

29 OCT 2026

STANDARD DEPARTURE CHART INSTRUMENT (SID) - ICAO

VILNIUS (EYVI) RNAV RWY 19

ATMEZ 1B, DUKAT 1B, ELEKA 1B, LAFAT 1B, SOGBI 1B, UPASI 1B

TRANSITION ALT 5000

TWR 118.205
APP 120.705
ATIS 125.805

ELEV, ALT IN FT
DIST IN NM
BRG, TRACK ARE MAG(TRUE)
VAR 9°E(2026)

COM FAILURE
SET TRANSPONDER CODE 7600.
CONTINUE SID ROUTES FOR AT LEAST 7 MIN CLIMBING TO LAST ASSIGNED AND ACKNOWLEDGED FL, BUT NOT BELOW FL120.
CONTINUE CLIMBING TO FPL FL.

RNAV 1
GNSS or DME/DME required

MSA
2700
FM ARP EYVI
25 NM

ATMEZ
ELEKA
LAFAT
UPASI
DUKAT
SOGBI

VI201 4000 MAX IAS 230 KT
VI202 FL075
VI203 FL120
VI204
VI205 FL110
VI206
VI207
VI208 FL180
VI209 FL140

ATMEZ 1B
ELEKA 1B
LAFAT 1B
DUKAT 1B
UPASI 1B
SOGBI 1B

PABERZE DME CH 119Y PBZ 800

SEMELISKES DME CH 72X SML 800

VILNIUS DVOR/DME 113.8 CH 85X VNO 700

VALKININKAI DME CH 114X VLK 700

EYTSA2B 4000 MSL 1200 MSL
EYTSA2C 4000 MSL 3000 MSL
EYTSA6 FL 150 FL 065
EYTSA1 4000 MSL 2000 MSL

EYP26 1600 MSL GND
EYP30 1600 MSL GND
EYP6 1600 MSL GND
EYP46 1600 MSL GND
EYP22 1600 MSL GND
EYP5 2000 MSL GND
EYP33 1000 MSL GND
EYD40 2000 MSL GND
EYD41 9400 MSL GND
EYD39 9400 MSL GND
EYD42 9400 MSL GND
EYD43 24000 MSL GND
EYD44 5200 MSL GND

SGZ PALUKNYS FL 065 GND

RŪDIŠKĖS
PALUKNYS/AV
KYVIŠKĖS
VILNIUS

VILNIUS EYVL FIR/UIR
MINSK UMMV FIR
Belarus

SCALE 1 : 500 000
0 5 10 15 20 Km
0 2.5 5 10 NM

For data tabulation see verso

©2019 ORO NAVIGACIJA

AIRAC AMDT 04/26

STANDARD DEPARTURE CHART INSTRUMENT (SID) - ICAO

TRANSITION ALT 5000

VILNIUS (EYVI) RNAV RWY 19

ATMEZ 1B, DUKAT 1B, ELEKA 1B, LAFAT 1B, SOGBI 1B, UPASI 1B

TABULAR DESCRIPTION

ATMEZ 1B PDG 7.0% REQUIRED DUE TO OPERATIONAL REASONS UNTIL VI201

Serial Number	*Path Descriptor*	*Waypoint Identifier*	*Fly-over*	*Course/Track °M(°T)*	*Magnetic Variation*	*Distance (NM)*	*Turn Direction*	*Altitude (FT)/ Flight level*	*Speed (KT)*	*Navigation Specification*
001	CF	VI201	—	193(201.9)	8.9	8.0	—	+4000	-230	RNAV1
002	TF	VI202	—	276(285.0)	8.9	8.6	—	+FL075	—	RNAV1
003	TF	VI203	—	002(010.4)	8.9	10.4	—	+FL120	—	RNAV1
004	TF	ATMEZ	—	002(010.4)	8.8	36.8	—	—	—	RNAV1

DUKAT 1B PDG 7.0% REQUIRED DUE TO OPERATIONAL REASONS UNTIL VI201

Serial Number	*Path Descriptor*	*Waypoint Identifier*	*Fly-over*	*Course/Track °M(°T)*	*Magnetic Variation*	*Distance (NM)*	*Turn Direction*	*Altitude (FT)/ Flight level*	*Speed (KT)*	*Navigation Specification*
001	CF	VI201	—	193(201.9)	8.9	8.0	—	+4000	-230	RNAV1
002	TF	VI204	—	103(111.8)	8.9	5.6	—	—	—	RNAV1
003	TF	DUKAT	—	078(086.5)	8.9	9.7	—	+FL110	—	RNAV1

ELEKA 1B PDG 7.0% REQUIRED DUE TO OPERATIONAL REASONS UNTIL VI201

Serial Number	*Path Descriptor*	*Waypoint Identifier*	*Fly-over*	*Course/Track °M(°T)*	*Magnetic Variation*	*Distance (NM)*	*Turn Direction*	*Altitude (FT)/ Flight level*	*Speed (KT)*	*Navigation Specification*
001	CF	VI201	—	193(201.9)	8.9	8.0	—	+4000	-230	RNAV1
002	TF	VI202	—	276(285.0)	8.9	8.6	—	+FL075	—	RNAV1
003	TF	VI203	—	002(010.4)	8.9	10.4	—	+FL120	—	RNAV1
004	TF	ELEKA	—	289(297.8)	8.5	12.5	—	—	—	RNAV1

LAFAT 1B PDG 7.0% REQUIRED DUE TO OPERATIONAL REASONS UNTIL VI201

Serial Number	*Path Descriptor*	*Waypoint Identifier*	*Fly-over*	*Course/Track °M(°T)*	*Magnetic Variation*	*Distance (NM)*	*Turn Direction*	*Altitude (FT)/ Flight level*	*Speed (KT)*	*Navigation Specification*
001	CF	VI201	—	193(201.9)	8.9	8.0	—	+4000	-230	RNAV1
002	TF	VI204	—	103(111.8)	8.9	5.6	—	—	—	RNAV1
003	TF	VI205	—	013(022.1)	8.9	9.7	—	+FL110	—	RNAV1
004	TF	VI206	—	013(022.2)	8.9	12.4	—	—	—	RNAV1
005	TF	LAFAT	—	067(076.2)	8.9	7.1	—	—	—	RNAV1

SOGBI 1B PDG 7.0% REQUIRED DUE TO OPERATIONAL REASONS UNTIL VI201

Serial Number	*Path Descriptor*	*Waypoint Identifier*	*Fly-over*	*Course/Track °M(°T)*	*Magnetic Variation*	*Distance (NM)*	*Turn Direction*	*Altitude (FT)/ Flight level*	*Speed (KT)*	*Navigation Specification*
001	CF	VI201	—	193(201.9)	8.9	8.0	—	+4000	-230	RNAV1
002	TF	VI202	—	276(285.0)	8.9	8.6	—	+FL075	—	RNAV1
003	TF	VI207	—	241(249.8)	8.5	9.0	—	—	—	RNAV1
004	TF	VI208	—	151(159.6)	8.4	14.0	—	+FL180	—	RNAV1
005	TF	SOGBI	—	095(103.8)	8.5	12.5	—	—	—	RNAV1

FOR DETAILED FLIGHT PROCEDURES REFER TO AIP EYVI AD 2.22

Changes: VAR; Procedures courses.

©2019 ORO NAVIGACIJA

STANDARD DEPARTURE CHART INSTRUMENT (SID) - ICAO

TRANSITION ALT 5000

VILNIUS (EYVI) RNAV RWY 19

ATMEZ 1B, DUKAT 1B, ELEKA 1B, LAFAT 1B, SOGBI 1B, UPASI 1B

TABULAR DESCRIPTION

UPASI 1B PDG 7.0% REQUIRED DUE TO OPERATIONAL REASONS UNTIL VI201

Serial Number	*Path Descriptor*	*Waypoint Identifier*	*Fly-over*	*Course/Track °M(°T)*	*Magnetic Variation*	*Distance (NM)*	*Turn Direction*	*Altitude (FT)/ Flight level*	*Speed (KT)*	*Navigation Specification*
001	CF	VI201	—	193(201.9)	8.9	8.0	—	+4000	-230	RNAV1
002	TF	VI202	—	276(285.0)	8.9	8.6	—	+FL075	—	RNAV1
003	TF	VI209	—	241(249.8)	8.4	14.3	—	+FL140	—	RNAV1
004	TF	UPASI	—	241(249.5)	8.3	11.0	—	+FL180	—	RNAV1

Passing 2500 FT MSL contact with Vilnius APP Channel 120.705

WAYPOINT COORDINATES			
FIX/POINTS	**COORDINATES**	**FIX/POINTS**	**COORDINATES**
VI201	54 29 48.5N 025 11 27.2E	**ATMEZ**	55 18 20.9N 025 12 04.7E
VI202	54 32 01.0N 024 57 11.3E	**DUKAT**	54 28 17.3N 025 36 55.2E
VI203	54 42 13.8N 025 00 25.2E	**ELEKA**	54 48 01.6N 024 41 20.1E
VI204	54 27 43.3N 025 20 21.8E	**LAFAT**	54 49 52.0N 025 46 43.0E
VI205	54 36 41.4N 025 26 39.2E	**SOGBI**	54 12 47.0N 025 11 45.0E
VI206	54 48 10.6N 025 34 46.6E	**UPASI**	54 23 12.1N 024 16 37.3E
VI207	54 28 54.2N 024 42 42.7E	**PBZ**	54 55 38.0N 025 14 23.0E
VI208	54 15 48.2N 024 51 01.3E	**SML**	54 40 31.2N 024 41 32.4E
VI209	54 27 03.5N 024 34 12.1E	**VLK**	54 21 02.9N 024 48 13.2E
		VNO	54 38 09.8N 025 17 37.1E

FOR DETAILED FLIGHT PROCEDURES REFER TO AIP EYVI AD 2.22

Changes: VAR; Procedures courses.

©2019 ORO NAVIGACIJA